



RUNDROHRE

EN AW-6060 T66 - EN 573-3, 755-1/-2/-8 | gepresst in Herstellungslängen von ca. 6 m



| D x S mm | kg/m | 6060 |
|----------|-------|------|
| 6 x 1,0 | 0,044 | ● |
| 8 x 1,0 | 0,061 | ● |
| 8 x 1,5 | 0,092 | ● |
| 10 x 1,0 | 0,085 | ● |
| 10 x 1,5 | 0,110 | ● |
| 10 x 2,0 | 0,141 | ● |
| 12 x 1,0 | 0,100 | ● |
| 12 x 1,5 | 0,139 | ● |
| 12 x 2,0 | 0,176 | ● |
| 12 x 3,0 | 0,238 | ● |
| 13 x 1,0 | 0,110 | ○ |
| 13 x 1,5 | 0,154 | ● |
| 14 x 1,5 | 0,169 | ○ |
| 14 x 2,0 | 0,212 | ● |
| 15 x 1,0 | 0,123 | ● |
| 15 x 1,5 | 0,178 | ● |
| 15 x 2,0 | 0,229 | ● |
| 16 x 1,0 | 0,132 | ○ |
| 16 x 1,5 | 0,191 | ● |
| 16 x 2,0 | 0,247 | ● |
| 16 x 2,5 | 0,297 | ○ |
| 16 x 3,0 | 0,358 | ○ |
| 18 x 1,0 | 0,149 | ○ |
| 18 x 1,5 | 0,218 | ○ |
| 18 x 2,0 | 0,281 | ● |
| 18 x 3,0 | 0,388 | ○ |
| 18 x 4,0 | 0,495 | ○ |
| 19 x 1,0 | 0,159 | ○ |
| 20 x 1,0 | 0,167 | ○ |
| 20 x 1,5 | 0,244 | ● |
| 20 x 2,0 | 0,316 | ● |
| 20 x 2,5 | 0,385 | ○ |
| 20 x 3,0 | 0,449 | ● |
| 20 x 4,0 | 0,558 | ● |
| 20 x 5,0 | 0,656 | ● |
| 22 x 1,0 | 0,185 | ○ |
| 22 x 1,5 | 0,271 | ● |
| 22 x 2,0 | 0,353 | ● |
| 22 x 3,0 | 0,500 | ○ |



RUNDROHRE

EN AW-6060 T66 - EN 573-3, 755-1/-2/-8 | gepresst in Herstellungslängen von ca. 6 m



| D x S mm | kg/m | 6060 |
|----------|-------|------|
| 24 x 1,5 | 0,297 | ○ |
| 25 x 1,0 | 0,212 | ○ |
| 25 x 1,5 | 0,310 | ● |
| 25 x 2,0 | 0,404 | ● |
| 25 x 2,5 | 0,495 | ● |
| 25 x 3,0 | 0,581 | ● |
| 25 x 5,0 | 0,880 | ● |
| 26 x 3,0 | 0,607 | ○ |
| 27 x 2,0 | 0,446 | ○ |
| 28 x 1,5 | 0,350 | ● |
| 28 x 2,0 | 0,457 | ● |
| 28 x 2,5 | 0,560 | ○ |
| 28 x 3,0 | 0,660 | ○ |
| 28 x 4,0 | 0,844 | ○ |
| 30 x 1,0 | 0,256 | ○ |
| 30 x 1,5 | 0,376 | ● |
| 30 x 2,0 | 0,492 | ● |
| 30 x 2,5 | 0,604 | ● |
| 30 x 3,0 | 0,712 | ● |
| 30 x 4,0 | 0,914 | ○ |
| 30 x 5,0 | 1,099 | ● |
| 32 x 1,0 | 0,271 | ○ |
| 32 x 1,5 | 0,402 | ● |
| 32 x 2,0 | 0,528 | ● |
| 32 x 3,0 | 0,765 | ○ |
| 33 x 2,0 | 0,540 | ○ |
| 33 x 4,5 | 1,108 | ● |
| 34 x 2,0 | 0,560 | ○ |
| 35 x 1,5 | 0,442 | ○ |
| 35 x 2,0 | 0,580 | ● |
| 35 x 2,5 | 0,714 | ○ |
| 35 x 3,0 | 0,844 | ● |
| 35 x 4,0 | 1,090 | ● |
| 35 x 5,0 | 1,319 | ● |
| 36 x 2,0 | 0,610 | ● |
| 38 x 1,5 | 0,481 | ○ |
| 38 x 2,0 | 0,633 | ○ |
| 38 x 3,0 | 0,923 | ○ |
| 38 x 4,0 | 1,200 | ○ |



RUNDROHRE

EN AW-6060 T66 - EN 573-3, 755-1/-2/-8 | gepresst in Herstellungslängen von ca. 6 m



| D x S mm | kg/m | 6060 |
|-----------|-------|------|
| 38 x 5,0 | 1,451 | ○ |
| 40 x 1,0 | 0,343 | ○ |
| 40 x 1,5 | 0,508 | ○ |
| 40 x 2,0 | 0,668 | ● |
| 40 x 2,5 | 0,824 | ● |
| 40 x 3,0 | 0,973 | ● |
| 40 x 4,0 | 1,266 | ○ |
| 40 x 5,0 | 1,539 | ● |
| 40 x 6,0 | 1,790 | ● |
| 40 x 8,0 | 2,220 | ○ |
| 40 x 10,0 | 2,638 | ● |
| 42 x 1,5 | 0,534 | ● |
| 42 x 2,0 | 0,703 | ○ |
| 42 x 2,5 | 0,868 | ○ |
| 42 x 3,0 | 1,029 | ○ |
| 42 x 3,5 | 1,185 | ○ |
| 42 x 4,0 | 1,336 | ○ |
| 45 x 1,5 | 0,574 | ● |
| 45 x 2,0 | 0,756 | ● |
| 45 x 2,5 | 0,934 | ● |
| 45 x 3,0 | 1,108 | ● |
| 45 x 4,0 | 1,442 | ○ |
| 45 x 5,0 | 1,758 | ● |
| 46 x 3,0 | 1,134 | ○ |
| 48 x 2,0 | 0,810 | ○ |
| 48 x 2,5 | 1,044 | ○ |
| 48 x 3,0 | 1,187 | ○ |
| 48 x 4,0 | 1,584 | ○ |
| 50 x 1,0 | 0,460 | ○ |
| 50 x 1,5 | 0,640 | ● |
| 50 x 2,0 | 0,844 | ● |
| 50 x 2,5 | 1,044 | ○ |
| 50 x 3,0 | 1,240 | ● |
| 50 x 4,0 | 1,618 | ○ |
| 50 x 5,0 | 1,978 | ● |
| 50 x 6,0 | 2,200 | ● |
| 50 x 8,0 | 2,865 | ○ |
| 50 x 10,0 | 3,517 | ● |

● Lagervorrat | ○ kurzfristig lieferbar



RUNDROHRE

EN AW-6060 T66 - EN 573-3, 755-1/-2/-8 | gepresst in Herstellungslängen von ca. 6 m



| D x S mm | kg/m | 6060 |
|-----------|-------|------|
| 54 x 2,0 | 0,915 | ○ |
| 55 x 1,5 | 0,699 | ○ |
| 55 x 2,0 | 0,932 | ● |
| 55 x 2,5 | 1,154 | ○ |
| 55 x 5,0 | 2,198 | ○ |
| 56 x 3,0 | 1,400 | ○ |
| 58 x 3,0 | 1,451 | ○ |
| 60 x 1,5 | 0,771 | ○ |
| 60 x 2,0 | 1,020 | ● |
| 60 x 2,5 | 1,264 | ● |
| 60 x 3,0 | 1,506 | ● |
| 60 x 4,0 | 1,969 | ● |
| 60 x 5,0 | 2,418 | ● |
| 60 x 6,0 | 2,849 | ○ |
| 60 x 10,0 | 4,396 | ● |
| 60 x 15,0 | 5,940 | ○ |
| 65 x 2,0 | 1,108 | ○ |
| 65 x 2,5 | 1,374 | ● |
| 65 x 5,0 | 2,638 | ● |
| 65 x 10,0 | 4,800 | ○ |
| 70 x 2,0 | 1,196 | ● |
| 70 x 3,0 | 1,767 | ○ |
| 70 x 4,0 | 2,322 | ○ |
| 70 x 5,0 | 2,857 | ● |
| 70 x 10,0 | 5,275 | ● |
| 70 x 15,0 | 7,245 | ○ |
| 70 x 20,0 | 8,650 | ○ |
| 75 x 2,5 | 1,594 | ● |
| 75 x 5,0 | 3,077 | ● |
| 75 x 10,0 | 5,664 | ○ |
| 76 x 2,5 | 1,616 | ○ |
| 76 x 3,0 | 1,925 | ● |
| 80 x 1,3 | 0,884 | ● |
| 80 x 1,5 | 1,030 | ○ |
| 80 x 2,0 | 1,372 | ● |
| 80 x 2,5 | 1,703 | ○ |
| 80 x 3,0 | 2,031 | ● |
| 80 x 4,0 | 2,673 | ○ |

● Lagervorrat | ○ kurzfristig lieferbar



RUNDROHRE

EN AW-6060 T66 - EN 573-3, 755-1/-2/-8 | gepresst in Herstellungslängen von ca. 6 m



RUNDROHRE

EN AW-6060 T66 - EN 573-3, 755-1/-2/-8 | gepresst in Herstellungslängen von ca. 6 m



| D x S mm | kg/m | 6060 |
|------------|--------|------|
| 80 x 5,0 | 3,297 | ● |
| 80 x 10,0 | 6,154 | ○ |
| 80 x 15,0 | 8,400 | ○ |
| 80 x 20,0 | 10,540 | ○ |
| 84 x 2,0 | 1,442 | ○ |
| 85 x 5,0 | 3,517 | ○ |
| 86 x 3,0 | 2,189 | ○ |
| 90 x 2,0 | 1,547 | ○ |
| 90 x 3,0 | 2,295 | ○ |
| 90 x 4,0 | 3,020 | ○ |
| 90 x 5,0 | 3,737 | ● |
| 90 x 10,0 | 7,034 | ● |
| 90 x 15,0 | 10,030 | ○ |
| 90 x 20,0 | 12,200 | ○ |
| 100 x 2,0 | 1,723 | ● |
| 100 x 2,5 | 2,143 | ○ |
| 100 x 3,0 | 2,558 | ○ |
| 100 x 4,0 | 3,376 | ● |
| 100 x 5,0 | 4,176 | ● |
| 100 x 8,0 | 6,430 | ○ |
| 100 x 10,0 | 7,913 | ● |
| 100 x 15,0 | 11,060 | ○ |
| 100 x 20,0 | 14,190 | ○ |
| 100 x 25,0 | 17,740 | ○ |
| 105 x 2,5 | 2,260 | ○ |
| 106 x 3,0 | 2,717 | ○ |
| 108 x 3,0 | 2,750 | ○ |
| 108 x 4,0 | 3,657 | ○ |
| 110 x 2,0 | 1,860 | ○ |
| 110 x 3,0 | 2,822 | ○ |
| 110 x 5,0 | 4,616 | ● |
| 110 x 10,0 | 8,792 | ● |
| 110 x 15,0 | 12,440 | ○ |
| 115 x 5,0 | 4,840 | ○ |
| 120 x 2,0 | 2,070 | ○ |
| 120 x 3,0 | 3,086 | ○ |
| 120 x 4,0 | 4,079 | ○ |
| 125 x 8,0 | 2,250 | ○ |

| D x S mm | kg/m | 6060 |
|------------|--------|------|
| 120 x 8,0 | 7,878 | ○ |
| 120 x 10,0 | 9,670 | ○ |
| 125 x 2,5 | 2,680 | ○ |
| 125 x 3,0 | 3,196 | ○ |
| 125 x 4,0 | 4,255 | ○ |
| 128 x 8,0 | 2,255 | ● |
| 125 x 10,0 | 10,111 | ○ |
| 130 x 3,0 | 3,350 | ● |
| 130 x 5,0 | 5,495 | ● |
| 130 x 10,0 | 10,550 | ○ |
| 130 x 15,0 | 15,116 | ○ |
| 133 x 3,0 | 3,425 | ○ |
| 133 x 4,0 | 4,570 | ○ |
| 138 x 3,0 | 3,570 | ○ |
| 140 x 4,0 | 4,780 | ○ |
| 140 x 5,0 | 5,935 | ● |
| 140 x 15,0 | 16,590 | ○ |
| 140 x 20,0 | 21,510 | ○ |
| 150 x 2,0 | 2,605 | ○ |
| 150 x 3,0 | 3,877 | ● |
| 150 x 5,0 | 6,374 | ● |
| 150 x 10,0 | 12,309 | ○ |
| 150 x 15,0 | 17,770 | ○ |
| 150 x 20,0 | 23,020 | ○ |
| 156 x 3,0 | 4,036 | ○ |
| 160 x 3,0 | 4,150 | ○ |
| 160 x 4,0 | 5,486 | ○ |
| 160 x 5,0 | 6,814 | ○ |
| 170 x 5,0 | 7,265 | ● |
| 180 x 5,0 | 7,730 | ○ |
| 200 x 5,0 | 8,752 | ○ |
| 200 x 10,0 | 16,705 | ○ |
| 200 x 15,0 | 25,350 | ○ |
| 200 x 20,0 | 32,100 | ○ |
| 220 x 5,0 | 9,220 | ○ |
| 220 x 10,0 | 18,490 | ○ |
| 250 x 5,0 | 9,604 | ○ |
| 250 x 10,0 | 21,101 | ○ |

● Lagervorrat | ○ kurzfristig lieferbar

● Lagervorrat | ○ kurzfristig lieferbar



RUNDROHRE



EN AW-6060 T66 - EN 573-3, 755-1/-2/-8 | gepresst in Herstellungslängen von ca. 6 m

| D x S mm | kg/m | 6060 |
|-------------|--------|------|
| 250 x 15,0 | 31,490 | ○ |
| 250 x 20,0 | 40,500 | ○ |
| 258 x 4,0 | 10,270 | ○ |
| 300 x 4,0 | 10,417 | ○ |
| 300 x 10,0 | 25,497 | ○ |
| 300 x 15,0 | 38,900 | ○ |
| 400 x 20,0 | 69,500 | ○ |

- Lagervorrat | ○ kurzfristig lieferbar